

Product Data

Outstanding Protection for Interior & Exterior Surfaces

Belzona® 5151/ 5131 (EG-Cladding/ Hi-Build Cladding) are coatings for long term waterproofing and weatherproofing of exterior and interior walls and structures.

Belzona® 5131 (EG-Cladding) also has built in energy conservation properties providing low thermal conductivity which together with exceptionally low heat capacity will make cold surfaces feel warm thus minimising condensation, and make warm surfaces feel cooler.

Belzona® 5131/ 5151 (EG-Cladding/ Hi-Build Cladding) will:

- Provide long term protection
- Prevent water penetration
- Reduce dirt retention
- Maintain building fabric insulation properties

Belzona® 5131/ 5151 (EG-Cladding/ Hi-Build Cladding) can be applied without the need for specialist tools and are suitable for use on porous and non-porous substrates.



Internal Walls



Metal Roofs

www.belzona.com

Belzona® provides the solution to your repair and maintenance needs.

Belzona® 5131/5151

EG-Cladding/ Hi-Build Cladding



Columns



Pipework

Applications for Belzona® 5151/ 5131 (EG-Cladding/ Hi-Build Cladding) include:

- External walls
- Internal walls
- Ducting and pipework
- Ceilings
- Metal roofs and cladding
- Cold pipework
- Lintels
- Columns


BELZONA®
Repair • Protect • Improve

Belzona® 5131/ 5151 are:

Simple

- Applied by brush or roller

Safe

- Cold temperature cure ensures no fire risk

Versatile

- Suitable for use on porous and non-porous substrates
- Can be applied to damp surfaces as micro-porosity allows substrate to dry out
- High flexible coating passing ASTM D522 1.5" conical mandrel and BS3900 : E1 0.5" cylindrical mandrel tests at temperatures as low as -24°C (14°F) thus accommodating normal building movements

Effective

- Excellent waterproofing characteristics
- Reflection and refraction of radiation from sunlight reduces heat built up providing long term protection
- Low carbon dioxide permeability drastically reduces carbonation
- Outstanding stability in aggressive environments
- Offers self cleaning properties on external walls


Belzona® 5131/5151

EG-Cladding/ Hi-Build Cladding



External Walls

For more information, please contact your local Belzona® representative:



QUALITY PRODUCTS - TECHNICAL SUPPORT

The Belzona® product range is manufactured through stringent quality and environmental control guidelines complying with the internationally recognised requirements of **ISO 9001:2008** and **ISO 14001:2004**.

Belzona® has a global distribution network of over 140 Distributors operating in 120 countries. Local support is provided by a trained Technical Consultant who will diagnose the problem, recommend the solution and provide 24 hour on-site application supervision and advice.



ISO 9001:2008
Q 09335
ISO 14001:2004
EMS 509612

Belzona products are manufactured under an ISO 9000 Registered Quality Management System

